

The following WhisperPower devices are supported by the OctoView 3"



Piccolo / Scalino Genverter with PMG frame 1 *



Battery Monitor Smart Shunt Pro



Battery Voltage Monitor



Supreme Combi Inverter/Charger 12V 3000W **



Battery Charger DC PowerCube



Inverter AC PowerCube



Battery Charger Supreme Pro

* PMG Frame 1 must have firmware version 2.00 or higher
** Supreme Combi must have WhisperConnect and firmware version A2.4, B0.8, C1.2 or higher



whisperpower.com



Scan me!



Control your Generator
Wherever you are...



whisperpower.com

Introducing OctoView 3"

Smart, Compact, and Versatile



The OctoView 3 Inch is a powerful and compact display that enhances local monitoring and control, making your energy system—and your generator—smarter. Designed for both marine and land-based applications, its durable build ensures reliable performance in any environment. With an intuitive interface and easy installation, the OctoView 3 transforms your generator into an intelligent, user-friendly system, allowing seamless monitoring and efficient management of connected devices.

OFFLINE MONITORING & CONTROL



For local control of your generator, without an internet connection, the OctoView 3 is a valuable tool. It allows users to check battery levels, adjust shore current limits, and control WhisperPower generators—all with a simple press of a button. Thanks to WhisperConnect CAN bus communication, multiple devices can be monitored and managed locally, making it an ideal choice for local control of your on board generator and/ or power system.

ONLINE MONITORING & CONTROL



Remote control of your generator is now available and easy to configure by adding the OctoControl Gateway to your system. Cloud connected, monitor and control your generator and/ or power system from wherever you are. By smart phone, laptop or PC, you have full control, always and everywhere. When connected online, the OctoView 3 enhances your control and accessibility.



OctoView 3

Art. Number 40280114

Specifications	
Display	2.8 inch, 320x240 pixels, full colour TFT
Dimensions	85 x 78 x 31 mm
Weight	<0,5 kg
Protection degree	IP20
Mounting	Panel mount (cutout: Ø65 mm, 4 screws included)

Integrated into a WhisperPower system, it automatically detects and displays all connected devices via the WhisperConnect network. The configuration wizard simplifies setup, ensuring a hassle-free experience. Whether used for standalone monitoring or as part of a larger energy management system, the OctoView 3 offers convenience, efficiency, and seamless connectivity.